

03-100

General Paint.

Interior Lacquer Sanding Sealer

INTENDED USES:

A clear, fast-drying sealer with excellent sanding properties, for use under clear lacquer finishes.

PRODUCT DESCRIPTION:

Clear nitrocellulose lacquer.

TECHNICAL INFORMATION:

Finish:

Flat

Tint Range:

N/A

Theoretical Coverage:

12-18 m²/3.7L (130-190 ft²/3.7L)

Typical Specific Gravity:

0.9

Application Thinner:

Not normally required.

Standard Colours:

Clear

Recommended # of coats:

1-2 at recommended coverage

Typical Volume Solids:

12%

Flash point:

6°C (43°F)

Clean-up Thinner:

Lacquer Thinner

SURFACE PREPARATION:

Wood must be clean, dry and free from dust, grease, mildew and wax.

APPLICATION:

Air or Airless Spray (Brush may be used for small areas)

Airless Tips: .009" - .013"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15-30 minutes
To Handle:	30 minutes - 1 hour
To Overcoat:	1 hour minimum

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

Flammable: This product is flammable. Do not smoke when using this product and ensure that there are no ignition sources (i.e. pilot lights, gas appliances, power tools and other electrical devices) in the area of use. Do not use in confined areas without the proper safety precautions/equipment.

ADDITIONAL DATA:

DO NOT USE 25-Line Woodcraft Urethane or Varnishes, or 75-Line Polyurethane over 03-100 Sanding Sealer.

Complies with the requirements of MPI #84.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.