

74-LINE



Platinum Acrylic Stain - Warranty Series

INTENDED USES:

A quick drying, densely pigmented, mildew resistant latex stain for exterior smooth or rough siding, cement fibre board, shakes and shingles. Ideally suited for new or previously stained wood which can be used for low temperature application.

PRODUCT DESCRIPTION:

Light fast pigments dispersed in a premium 100% acrylic latex. Formulated using coloured bases to improve the hiding and fade resistance of the darker coloured stains.

TECHNICAL INFORMATION:

Finish:

Flat

Standard Colours:

White

Tint Range:

Full Range of Colours including 141 Standard Stain Colours

Recommended # of coats:

1-2 at recommended coverage

Theoretical Coverage:

24-33 m²/3.7L (260-350 ft²/3.7L)

Typical Volume Solids:

33%

Typical Specific Gravity:

1.2

Flash point:

Not Applicable

Application Thinner:

Not normally required. Up to 10% water may be used, if required, for spraying.

Clean-up Thinner:

Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint.

Ensure all joints and seams are filled with a paintable caulking to prevent moisture ingress. Surface repairs should be spot primed.

New Wood: Primer not required, but when using white or a light colour prime with 32-002 Exterior Oil Primer to prevent tannin staining.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .011" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

| | |
|--------------|---------------------------------------|
| To Touch: | 15-60 minutes |
| To Handle: | 1-2 hours |
| To Overcoat: | 4 hours (takes 28 days to fully cure) |

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

*Brushing is preferred because the stain is worked into the surface and a more uniform distribution is achieved. To avoid lap marks, keep a "wet" edge by stopping only at natural breaks. May be applied to slightly damp (not wet) surfaces. Do not use on roofs or decks. Not recommended over glossy surfaces or previously painted surfaces. For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting.

Drying time will vary depending on temperature, air circulation and humidity. The surface and air temperature must remain above 2°C while the humidity remains below 70%. If painting in cold conditions the temperature must not fall below freezing for at least 8 hours. Recoat time at lower temperatures requires a minimum of 24 hours when temperatures are below 10°C. Do not apply if snow, rain, frost, fog or damp conditions are expected within 24 hours after application.

Legal Details

The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied, is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.