

Product  
**11-011**  
Interior/Exterior  
Quick Dry  
Plastic Primer

### INTENDED USES:

A fast drying interior/exterior primer used to obtain a good bond on surfaces which typically present problems in achieving good adhesion. The use of this product will reduce the requirement to sand surface. Can be used on metal, millwork, trim, hard board, particle board, plastic, Fiberglas, tile and ceramics. Offers excellent sanding properties and hold-out under enamels and lacquer.

### PRODUCT DESCRIPTION:

A fast drying resin pigmented with inert pigments and fast evaporating solvents.

### TECHNICAL INFORMATION:

|                                  |  |
|----------------------------------|--|
| <b>Finish:</b>                   | Flat   |
| <b>Standard Colours:</b>         | White  |
| <b>Tint Range:</b>               | Light Millennium colours                                   |
| <b>Recommended # of coats:</b>   | 1-2 at recommended coverage                                |
| <b>Theoretical Coverage:</b>     | 32-43 m <sup>2</sup> /3.7L (350-460 ft <sup>2</sup> /3.7L) |
| <b>Typical Volume Solids:</b>    | 43%  |
| <b>Typical Specific Gravity:</b> | 1.4  |
| <b>Flash point:</b>              | 28°C (82°F)  |
| <b>Application Thinner:</b>      | Spray - Thin up to 20% with Toluene or Xylene              |
| <b>Clean-up Thinner:</b>         | Toluene or Xylene  |

### SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint.

### APPLICATION:

Air or Airless Spray (Brush may be used for small areas)

Airless Tips: .011" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

|              |   |
|--------------|---|
| To Touch:    | 10 minutes  |
| To Handle:   | 30 minutes  |
| To Overcoat: | Min. 30 min. for latex and alkyds. Min. 2 hours for lacquers and Industrial finishes. |

### PRODUCT HAZARDS \_SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

Flammable: This product is flammable. Do not smoke when using this product and ensure that there are no ignition sources (i.e. pilot lights, gas appliances, power tools and other electrical devices) in the area of use. Do not use in confined areas without the proper safety precautions/equipment.

### ADDITIONAL DATA:

Suitable for painting schedules where fast recoating is essential. This primer dries to a very hard solvent resistant finish. Note: It is not designed for use as a primer on exterior wood siding.

Complies with the requirements of MPI #69.



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.