

INTENDED USES:

A flat finish paint for exterior use on shakes, shingled sidewalls, smooth or rough siding and fences.

PRODUCT DESCRIPTION:

A formulation of durable, light-fast pigments in a modified alkyd vehicle. Contains a strong fungicide to inhibit mildew growth.

TECHNICAL INFORMATION:

Finish:	Flat
Standard Colours:	White
Tint Range:	Full range of Millennium colours
Recommended # of coats:	1-2 at recommended coverage
Theoretical Coverage:	32-43 m ² /3.7L (350-460 ft ² /3.7L)
Typical Volume Solids:	43%
Typical Specific Gravity:	1.3
Flash point:	51°C (124°F)
Application Thinner:	Not normally required. Up to 10% Mineral Spirits for spraying.
Clean-up Thinner:	Mineral Spirits

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Ensure all joints and seams are filled with a paintable caulking to prevent moisture ingress. Prime as required. Surface repairs should be spot primed. New Wood: Prime with 32-002 Exterior Oil Primer. Previously Painted Surfaces: Glossy surfaces should be sanded to a dull finish to provide good adhesion. Spot prime any bare areas with 32-001 Ext. Alkyd Primer. Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray.

Airless Tips: .015" - .021"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	4-6 hours
To Handle:	8-12 hours
To Overcoat:	16 hours minimum

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and relative humidity are between 10-25°C and 40-60% respectively, at the time of application and for four hours afterward. Not recommended for roofing shingles. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. First coat on new wood should be brush applied if primer is not used.

Complies with the requirements of MPI #8.

Product
19-LINE
Premium Alkyd
Exterior Flat



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.