

Product
25-019
Marine Spar
Varnish

INTENDED USES:

A very high quality clear gloss exterior varnish for wood surfaces particularly those exposed to marine conditions. Recommended where colour is not a critical factor as on mahogany and other darker woods.

PRODUCT DESCRIPTION:

Pure phenolic resin/tung oil combination.

TECHNICAL INFORMATION:

Finish:	Gloss
Standard Colours:	Clear
Tint Range:	N/A
Recommended # of coats:	2-3 at recommended coverage
Theoretical Coverage:	35-47 m ² /3.7L (380-500 ft ² /3.7L)
Typical Volume Solids:	47%
Typical Specific Gravity:	0.9
Flash point:	42°C (108°F)
Application Thinner:	Mineral Spirits
Clean-up Thinner:	Mineral Spirits

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling varnish.

New Wood: Apply first coat thinned 10% with paint thinner and second coat as supplied.

Previously Coated Wood: Glossy surfaces should be sanded to a dull finish to provide good adhesion.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .011" - .015"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	2-4 hours
To Handle:	8-12 hours
To Overcoat:	16 hours minimum

PRODUCT HAZARDS _SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

Product has a darker tone, test on scrap or a small inconspicuous area for appearance before application.

Complies with the requirements of MPI #28.



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.