

Product
28-080
Tradesman
Interior Latex
Sealer

INTENDED USES:

A latex sealer for new drywall. Designed to provide exceptionally high hiding power combined with efficient sealing properties. Ideal for new construction where a two coat finish is required, and the finish coat is a low sheen product. Not recommended for use under higher sheen finishes.

PRODUCT DESCRIPTION:

A professional quality latex sealer formulated with titanium dioxide and inert pigments.

TECHNICAL INFORMATION:

Finish:	Flat
Standard Colours:	White
Tint Range:	Light Millennium colours
Recommended # of coats:	1-2 at recommended coverage
Theoretical Coverage:	22-30 m ² /3.7L (240-320 ft ² /3.7L)
Typical Volume Solids:	29%
Typical Specific Gravity:	1.3
Flash point:	Not Applicable
Application Thinner:	Water, if required for spraying.
Clean-up Thinner:	Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from loose material. Drywall joints and patched areas must be dry and free from sanding dust.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15 to 30 minutes
To Handle:	2 hours
To Overcoat:	3 hours minimum

PRODUCT HAZARDS _SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

Complies with the requirements of MPI #50.



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.