

Product
51-040
Interior Latex
Drywall Sealer

INTENDED USES:

A high opacity sealer designed for use on new drywall. Specially formulated to give high opacity for use over unbleached drywall. Ideal for use under flat or low sheen latex's. Not recommended under alkyd eggshell and semi-gloss finishes without an undercoat. For additional smoothness and film build under alkyd finishes, use 02-220 Enamel Undercoat.

PRODUCT DESCRIPTION:

A highly pigmented latex.

TECHNICAL INFORMATION:

Finish:	Flat
Standard Colours:	White
Tint Range:	Light Millennium colours
Recommended # of coats:	1-2 at recommended coverage
Theoretical Coverage:	22-29 m ² /3.7L (230-310 ft ² /3.7L)
Typical Volume Solids:	29%
Typical Specific Gravity:	1.3
Flash point:	Not Applicable
Application Thinner:	Water, if required for spraying
Clean-up Thinner:	Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from loose material. Drywall joints and patched areas must be dry and free from sanding dust.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .015" - .021"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15 to 30 minutes
To Handle:	2 hours
To Overcoat:	4 hours minimum

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.