

**INTENDED USES:**

A quick drying, high performance semi-gloss acrylic finish for interior applications in high wear areas where high maintenance is required. Designed for commercial applications where buildings may be occupied and a need is present for a low odour/low VOC product when repainting or renovation work is being done.

**PRODUCT DESCRIPTION:**

A high performance acrylic paint formulated to low VOC levels. The result is a low odour and more environmentally friendly product.

**TECHNICAL INFORMATION:**

<b>Finish:</b>	Semi-Gloss
<b>Standard Colours:</b>	White
<b>Tint Range:</b>	Light Millennium Colours*
<b>Recommended # of coats:</b>	1-2 at recommended coverage
<b>Theoretical Coverage:</b>	26-34 m <sup>2</sup> /3.78L (275-370 ft <sup>2</sup> /3.78L)
<b>Typical Volume Solids:</b>	35%
<b>Typical Specific Gravity:</b>	1.3
<b>Flash point:</b>	Not Applicable
<b>Application Thinner:</b>	Not normally required. Up to 10% water may be used, if required, for spraying.
<b>Clean-up Thinner:</b>	Water

**SURFACE PREPARATION:**

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Prime as required below. Surface repairs should be spot primed.

New Drywall: Seal with 51-087 Latex Super Seal.

New Wood: Prime with 70-002 Latex Wood Primer.

Previously Painted Surfaces: Glossy surfaces should be sanded to a dull finish or primed with 51-050 Latex Plastic Primer to provide good adhesion.

Metal and Other Surfaces: Consult your GP Paint Pro.

**APPLICATION:**

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15 to 30 minutes
To Handle:	1 hour
To Overcoat:	2-4 hours

**PRODUCT HAZARDS SAFETY INFORMATION:**

See Material Safety Data Sheet for complete Health and Safety information.

**ADDITIONAL DATA:**

For optimum adhesion and application performance, ensure that the temperature and



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. A curing period of 7-10 days is required before the optimum properties are achieved. Consult your GP Paint Pro.

\*Can be tinted with up to 4 ounces of colorant, however this will increase the VOC levels and may add some odour to the paint.