

Product
57-LINE
Kitchen & Bath
Semi-Gloss
Finish

INTENDED USES:

A quick drying semi-gloss finish with excellent adhesion to new surfaces and to previously painted latex and alkyd finishes. Specially formulated for kitchens, laundry rooms and bathrooms where moisture and condensation occur. May also be used in other areas where a very durable semi-gloss finish is required.

PRODUCT DESCRIPTION:

A suitably pigmented, high quality, 100% acrylic latex. Contains a fungicidal agent to inhibit mildew growth on the surface of the coating.

TECHNICAL INFORMATION:

Finish:	Semi-Gloss
Standard Colours:	White
Tint Range:	Full range of Millennium colours
Recommended # of coats:	1-2 at recommended coverage
Theoretical Coverage:	27-36 m ² /3.7L (290-390 ft ² /3.7L)
Typical Volume Solids:	36%
Typical Specific Gravity:	1.2
Flash point:	Not Applicable
Application Thinner:	Not required for brush or roller application. Water if necessary for spraying.
Clean-up Thinner:	Water

SURFACE PREPARATION:

Surfaces must be clean, dry and free from dust, grease, mildew and wax. Remove any loose and peeling paint and repair with patching compound. Prime as required below. Surface repairs should be spot primed.

New Drywall: Seal with 51-087 Latex Super Seal.

New Wood: Prime with 02-230 Alkyd Primer Sealer or 70-002 Latex Wood Primer.

Previously Painted Surfaces: Can be applied directly onto most surfaces but if glossy surfaces are sanded to a dull finish or primed with 51-050 Latex Plastic Primer the adhesion and application properties will be optimized.

Metal and Other Surfaces: Consult your GP Paint Pro.

APPLICATION:

Brush, Roller, Air Spray or Airless Spray

Airless Tips: .013" - .017"

Dry times at 21°C / 70°F and 40%-60% R.H.:

To Touch:	15 to 30 minutes
To Handle:	2 hours
To Overcoat:	4 hours minimum

PRODUCT HAZARDS SAFETY INFORMATION:

See Material Safety Data Sheet for complete Health and Safety information.

ADDITIONAL DATA:

For optimum adhesion and application performance, ensure that the temperature and



The information contained herein is true and accurate to the best of our knowledge. However, no guarantee or warranty of any kind, express or implied is given with respect to the accuracy or completeness of the said information and data or to the products described herein and we assume no risk or liability for the performance or coverage of or for injury resulting from the handling, use or application of the said information, data or products.

relative humidity are between 15-25°C and 40-60% respectively, at the time of application and for four hours afterward. If mildew is present, the surface should be washed with a chlorine bleach solution (20% household bleach and 1% liquid detergent in warm water) and thoroughly rinsed prior to painting. The coating should be allowed to dry for a minimum of 48 hrs. before subjecting to condensation and cured for 30 days before washing. If using inside cupboards where air circulation is poor, allow a minimum of 7 days before using.

For food cupboards, ensure that all traces of odour have dissipated before replacing food. Consult your GP Paint Pro.